

Sehr geehrte Damen und Herren,

wir erklären folgend die Zuordnung der Artikel zum beigefügten Sicherheitsdatenblatt.

Lieferant ist:

**DEKA Kleben & Dichten GmbH**

**Laufende Nummer aus dem Gefahrgutkataster:**

**137**

| Lieferantenartikelnummer | Movera Artikelnummer |
|--------------------------|----------------------|
| 1313MHA                  | 9944003              |

Bad Waldsee, 14. Januar 2019

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.11.2014

Version number 10

Revision: 30.01.2014

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

- Trade name: Dekaseal 8936 Lightgrey
- Article number: 62503+62511

**1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.

• Application of the substance / the mixture Sealant

**1.3 Details of the supplier of the safety data sheet**

• **Manufacturer/Supplier:**  
Dekalin, brand of Diffutherm B.V.  
Smaragdweg 50  
NL-5527 LB Hapert  
Tel: +31 497 551 080  
Fax: +31 497 551 088  
E-mail: info@dekalin.nl

• Further information obtainable from: Product safety Department

**1.4 Emergency telephone number:**

Tel: +31 497 551 080 (mo-fr/8.00-16.30)

National Poisons Information Center (NVIC)

TEL: +31 (0)30-2748888

Only for the purpose of informing medical personnel in cases of acute intoxications

Vergiftungsinformationszentrale Österreich, Tel.: +43 1 406 4343

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 2      H225 Highly flammable liquid and vapour.



GHS07

Skin Irrit. 2      H315 Causes skin irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



F; Highly flammable

R11:      Highly flammable.

R52/53:      Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

**2.2 Label elements**

• Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

• Hazard pictograms GHS02, GHS07

• Signal word Danger

• Hazard statements

H225 Highly flammable liquid and vapour.

(Contd. on page 2)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.11.2014

Version number 10

Revision: 30.01.2014

**Trade name: Dekaseal 8936 Lightgrey**

(Contd. of page 1)

H315 Causes skin irritation.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P243 Take precautionary measures against static discharge.

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**2.3 Other hazards**
**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

**3.2 Chemical characterization: Mixtures**
**Description:** Mixture of substances listed below with additions.

**Dangerous components:**

|  |   |         |
|--|---|---------|
| CAS: 64742-49-0<br>EC number: 921-024-6<br>Reg.nr.: 01-2119475514-35 | Naphtha (petroleum), hydrotreated light<br>☒ Xn R65; ☒ Xi R38; ☒ F R11; ☒ N R51/53<br>R67<br>☉ Flam. Liq. 2, H225; ☉ Asp. Tox. 1, H304; ☉ Aquatic Chronic 2, H411; ☉ Skin Irrit. 2, H315; STOT SE 3, H336 | 10-<25% |
| CAS: 64742-82-1<br>EINECS: 265-185-4                                 | Naphtha (petroleum), hydrodesulfurized heavy<br>☒ Xn R65; ☒ N R51/53<br>R10-66-67<br>☉ Flam. Liq. 3, H226; ☉ Asp. Tox. 1, H304; ☉ Aquatic Chronic 2, H411; ☉ STOT SE 3, H336                              | <1%     |

**Additional information:** For the wording of the listed risk phrases refer to section 16.

### SECTION 4: First aid measures

**4.1 Description of first aid measures**
**After skin contact:** If skin irritation continues, consult a doctor.

**After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:** If symptoms persist consult doctor.

**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### SECTION 5: Firefighting measures

**5.1 Extinguishing media**
**Suitable extinguishing agents:**

 CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**For safety reasons unsuitable extinguishing agents:** Water with full jet

**5.2 Special hazards arising from the substance or mixture** No further relevant information available.

**5.3 Advice for firefighters**
**Protective equipment:** Mount respiratory protective device.

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.11.2014

Version number 10

Revision: 30.01.2014

**Trade name: Dekaseal 8936 Lightgrey**

(Contd. of page 2)

· **Additional information** Cool endangered receptacles with water spray.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Prevent seepage into sewage system, workpits and cellars.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Use only in well ventilated areas.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**  
Storage:  
Requirements to be met by storerooms and receptacles: Store in a cool location.  
Information about storage in one common storage facility: Not required.  
Further information about storage conditions:  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs**

| 64742-49-0 Naphtha (petroleum), hydrotreated light |  |                                       |
|--|--|---------------------------------------|
| Oral   | Long-term - systemic effects, general population | 699 mg/kg bw/day (General Population) |
| Dermal   | Long-term - systemic effects, general population | 699 mg/kg bw/day (General population) |
|  | Long-term - systemic effects, worker             | 773 mg/kg bw/day (Worker)             |
| Inhalative   | Long-term - systemic effects, general population | 608 mg/m3 (General Population)        |
|  | Long-term - systemic effects, worker             | 2035 mg/m3 (Worker)                   |

· **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 4)

Trade name: Dekaseal 8936 Lightgrey

(Contd. of page 3)

- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.
- **Respiratory protection:**  
Use suitable respiratory protective device in case of insufficient ventilation.  
Short term filter device:



Filter AX

- **Protection of hands:**



Protective gloves

- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber

Recommended thickness of the material:  $\geq 0.12$  mm

- **Penetration time of glove material**

> 480 min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Use protective suit.

## SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

|                         |                 |
|-------------------------|-----------------|
| <b>Form:</b>            | Pasty           |
| <b>Colour:</b>          | Light grey      |
| <b>Odour:</b>           | Characteristic  |
| <b>Odour threshold:</b> | Not determined. |

- **pH-value:** Not determined.

- **Change in condition**

|                                     |               |
|-------------------------------------|---------------|
| <b>Melting point/Melting range:</b> | Undetermined. |
| <b>Boiling point/Boiling range:</b> | 60 °C         |

- **Flash point:** -1 °C (DIN 53213)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** > 200 °C

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.11.2014

Version number 10

Revision: 30.01.2014

**Trade name: Dekaseal 8936 Lightgrey**

(Contd. of page 4)

|   |   |
|---|---|
| · <b>Decomposition temperature:</b>               | Not determined.   |
| · <b>Self-igniting:</b>                           | Product is not selfigniting.  |
| · <b>Danger of explosion:</b>                     | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · <b>Explosion limits:</b>                        |   |
| Lower:  | 0.6 Vol %   |
| Upper:  | 7.0 Vol %   |
| · <b>Vapour pressure At 20 °C:</b>                | 61 hPa  |
| · <b>Density At 20 °C:</b>                        | 1.34 g/cm <sup>3</sup> (DIN 51757)  |
| · <b>Relative density</b>                         | Not determined.   |
| · <b>Vapour density</b>                           | Not determined.   |
| · <b>Evaporation rate</b>                         | Not determined.   |
| · <b>Solubility in / Miscibility with water:</b>  | Not miscible or difficult to mix.   |
| · <b>Partition coefficient (n-octanol/water):</b> | Not determined.   |
| · <b>Viscosity:</b>                               |   |
| Dynamic:  | Not determined.   |
| Kinematic:  | Not determined.   |
| · <b>Solvent content:</b>                         |   |
| Organic solvents:                                 | 12.5 %  |
| Water:  | 0.1 %   |
| Solids content:                                   | 87.3 % (DIN 53216)  |
| · <b>9.2 Other information</b>                    | No further relevant information available.  |
| · <b>VOC (EU):</b>                                | 12.54 %   |
| · <b>VOC (EU):</b>                                | 168.1 g/l   |
| · <b>VOCV:</b>                                    | 12.54 %   |

### SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

 · **LD/LC50 values relevant for classification:**
**ATE (Acute Toxicity Estimates)**

|            |          |                |
|------------|----------|----------------|
| Inhalative | LC50/4 h | 207 mg/l (RAT) |
|------------|----------|----------------|

**64742-49-0 Naphtha (petroleum), hydrotreated light**

|            |          |                      |
|------------|----------|----------------------|
| Oral       | LD50     | >5840 mg/kg (RAT)    |
| Dermal     | LD50     | >2920 mg/kg (RABBIT) |
| Inhalative | LC50/4 h | >25.2 mg/l (RAT)     |

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.11.2014

Version number 10

Revision: 30.01.2014

**Trade name: Dekaseal 8936 Lightgrey**

(Contd. of page 5)

**64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy**

|        |      |                      |
|--------|------|----------------------|
| Oral   | LD50 | >6500 mg/kg (RAT)    |
| Dermal | LD50 | >3000 mg/kg (RABBIT) |

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

### SECTION 12: Ecological information

**12.1 Toxicity**
**Aquatic toxicity:**
**64742-49-0 Naphtha (petroleum), hydrotreated light**

|           |   |
|-----------|---|
| EC50/48 h | 10 mg/l (PHAEOPHYTA)                              |
| EL50/48 h | 3 mg/l (DAPHNIA MAGNA)                            |
| EL50/72 h | 30-100 mg/l (SELENASTRUM CAPRICORNUTUM)           |
| LL50/96 h | 11.4 mg/l (SALMO GAIRDNERI / ONCORHYNCHUS MYKISS) |

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.  
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

**13.1 Waste treatment methods**
**Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**European waste catalogue**

|           |   |
|-----------|---|
| 08 00 00  | WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS |
| 08 04 00  | wastes from MFSU of adhesives and sealants (including waterproofing products)   |
| 08 04 09* | waste adhesives and sealants containing organic solvents or other dangerous substances  |

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

GB

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.11.2014


Version number 10

Revision: 30.01.2014

Trade name: Dekaseal 8936 Lightgrey

(Contd. of page 6)

### SECTION 14: Transport information

|   |   |
|---|---|
| <ul style="list-style-type: none"> <li>· 14.1 UN-Number</li> <li>· ADR, IMDG, IATA</li> </ul>   | UN1139  |
| <ul style="list-style-type: none"> <li>· 14.2 UN proper shipping name</li> <li>· ADR</li> <li>· IMDG, IATA</li> </ul>                         | 1139 COATING SOLUTION, special provision 640D<br>COATING SOLUTION   |
| <ul style="list-style-type: none"> <li>· 14.3 Transport hazard class(es)</li> <li>· ADR, IMDG, IATA</li> </ul>                                | <div style="text-align: center;">  </div>  |
| <ul style="list-style-type: none"> <li>· Class</li> <li>· Label</li> </ul>  | 3 Flammable liquids.<br>3   |
| <ul style="list-style-type: none"> <li>· 14.4 Packing group</li> <li>· ADR, IMDG, IATA</li> </ul>   | II  |
| <ul style="list-style-type: none"> <li>· 14.5 Environmental hazards:</li> <li>· Marine pollutant:</li> </ul>                                  | No  |
| <ul style="list-style-type: none"> <li>· 14.6 Special precautions for user</li> <li>· Danger code (Kemler):</li> <li>· EMS Number:</li> </ul> | Warning: Flammable liquids.<br>33<br>F-E,S-E  |
| <ul style="list-style-type: none"> <li>· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</li> </ul>              | Not applicable.   |
| <ul style="list-style-type: none"> <li>· Transport/Additional information:</li> </ul>   | Transport classification ADR/IMDG is based on packaging >30ltr(IMDG), <450ltr(ADR).<br>For other packaging units different classification can apply.<br>See ADR 2.2.3.1.3/ 2.2.3.1.4 und IMDG 2.3.2.3 / 2.3.2.5 |
| <ul style="list-style-type: none"> <li>· ADR</li> <li>· Limited quantities (LQ)</li> <li>· Excepted quantities (EQ)</li> </ul>                | 5L<br>Code: E2<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 500 ml   |
| <ul style="list-style-type: none"> <li>· Transport category</li> <li>· Tunnel restriction code</li> </ul>                                     | 2<br>D/E  |
| <ul style="list-style-type: none"> <li>· IMDG</li> <li>· Limited quantities (LQ)</li> <li>· Excepted quantities (EQ)</li> </ul>               | 5L<br>Code: E2<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 500 ml   |
| <ul style="list-style-type: none"> <li>· UN "Model Regulation":</li> </ul>  | UN1139, COATING SOLUTION, special provision 640D, 3, II   |

### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Labelling according to Regulation (EC) No 1272/2008  
The product is classified and labelled according to the CLP regulation.
- Hazard pictograms GHS02, GHS07
- Signal word Danger

(Contd. on page 8)



**Trade name: Dekaseal 8936 Lightgrey**

(Contd. of page 7)

· **Hazard statements**

- H225 *Highly flammable liquid and vapour.*  
H315 *Causes skin irritation.*  
H412 *Harmful to aquatic life with long lasting effects.*

· **Precautionary statements**

- P210 *Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*  
P243 *Take precautionary measures against static discharge.*  
P273 *Avoid release to the environment.*  
P280 *Wear protective gloves / protective clothing.*  
P303+P361+P353 *IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.*  
P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **National regulations:**

· **Technical instructions (air):**

| Class  | Share in % |
|--------|------------|
| Wasser | 0.1        |
| NK     | 12.5       |

- **Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.**  
· **15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**

**SECTION 16: Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Relevant phrases**

- H225 *Highly flammable liquid and vapour.*  
H226 *Flammable liquid and vapour.*  
H304 *May be fatal if swallowed and enters airways.*  
H315 *Causes skin irritation.*  
H336 *May cause drowsiness or dizziness.*  
H411 *Toxic to aquatic life with long lasting effects.*  
R10 *Flammable.*  
R11 *Highly flammable.*  
R38 *Irritating to skin.*  
R51/53 *Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*  
R65 *Harmful: may cause lung damage if swallowed.*  
R66 *Repeated exposure may cause skin dryness or cracking.*  
R67 *Vapours may cause drowsiness and dizziness.*

· **Department issuing MSDS: Product safety department.**

· **Contact: info@dekalin.nl**

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organization  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL: Derived No-Effect Level (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
Flam. Liq. 2: Flammable liquids, Hazard Category 2  
Flam. Liq. 3: Flammable liquids, Hazard Category 3

(Contd. on page 9)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 04.11.2014

Version number 10

Revision: 30.01.2014

**Trade name: Dekaseal 8936 Lightgrey**

(Contd. of page 8)

*Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2**STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3**Asp. Tox. 1: Aspiration hazard, Hazard Category 1**Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2**Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3**\* Data compared to the previous version altered.*

GB