



**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006

SDS # : 081072

**MAZDA ORIGINAL OIL ULTRA  
5W30**

Date of the previous version: 2012-08-31

Revision Date: 2015-04-14

Version 2

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

<b>Product name</b>	<b>MAZDA ORIGINAL OIL ULTRA 5W30</b>
<b>Number</b>	71Y
<b>Substance/mixture</b>	Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

<b>Identified uses</b>	Motor oil.
------------------------	------------

1.3. Details of the supplier of the safety data sheet

<b>Supplier</b>	TOTAL BELGIUM Handelsstraat, 93, Rue du Commerce B-1040 BRUSSEL - BRUXELLES België - Belgique Tel : +32 (0)22 889 933 Fax : +32 (0)22 883 260
-----------------	--

For further information, please contact:

Contact Point	HSE
E-mail Address	rm.be-reach-belgium-msds@total.com

1.4. Emergency telephone number

Official National Emergency Number:

Teleserv S.O.S Total Belgium : +32 (0)78 15 51 51  
On duty staff in Ertvelde (Lub): +32 (0)475 66 07 77

Burns Centers:

Bruxelles - (NOH) - Brussel : +32 (0)2 264 48 48, Hopital Militaire Reine Astrid - Militair Hospitaal Koningin Astrid  
Antwerpen - Anvers : +32 (0)3 217 71 11, Algemeen centrum Ziekenhuis  
Gent - Gand : +32 (0)9 240 34 90 Centre Universitaire UZ Gand-Universitair Ziekenhuis UZ Gent  
Leuven - Louvain : +32 (0)16 34 87 50 U.Z. Leuven  
Loverval : +32 (0)71 44 80 00, Hôpital Saint Joseph et Sainte Thérèse, section I.M.T.R  
Luik - Liège : +32 (0)4 366 72 94, CHU Liège domaine Universitaire du Sart Tilman



SDS # : 081072

# MAZDA ORIGINAL OIL ULTRA 5W30

Revision Date: 2015-04-14

Version 2

Poison center:  
c/o Hôpital Militaire Reine Astrid  
Militair Hospitaal Koningin Astrid  
1 Rue Bruyn - Bruynstraat 1  
B-1120 Bruxelles - Brussel  
+32 (0)70 245 245

## Section 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

#### REGULATION (EC) No 1272/2008 \*\*\*

*For the full text of the H-Statements mentioned in this Section, see Section 2.2. \*\*\**

#### Classification\*\*\*

The product is classified as dangerous in accordance with Regulation (EC) No. 1272/2008\*\*\*  
Serious eye damage/eye irritation - Category 2\*\*\* - (H319)\*\*\*

#### DIRECTIVE 67/548/EEC or 1999/45/EC

*For the full text of the R-phrases mentioned in this Section, see Section 16.*

The substance/mixture is non-dangerous in accordance with Directive(s) 67/548/EEC with amendments and/or 1999/45/EC with amendments

#### Symbol(s)

Not classified\*\*\*

### 2.2. Label elements

Labelled according to

REGULATION (EC) No 1272/2008\*\*\*



#### Signal Word

WARNING\*\*\*

#### Hazard Statements \*\*\*

H319 - Causes serious eye irritation\*\*\*

#### Precautionary statements

P280 - Wear eye protection/ face protection\*\*\*



SDS # : 081072

# MAZDA ORIGINAL OIL ULTRA 5W30

Revision Date: 2015-04-14

Version 2

## Supplemental Hazard Statements

EUH210 - Safety data sheet available on request\*\*\*

### 2.3. Other hazards

**Physical-Chemical Properties** Contaminated surfaces will be extremely slippery.

**Environmental properties** Should not be released into the environment.

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixture\*\*\*

#### Hazardous components

Chemical Name	EC-No	REACH Registration Number	CAS-No	Weight %	Classification (Dir. 67/548)	GHS Classification
Distillates (petroleum), hydrotreated heavy paraffinic***	265-157-1	01-2119484627-25	64742-54-7	<60	-	Asp. Tox. 1 (H304)
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)***	298-577-9* **	01-2119543726-33** *	93819-94-4	<1.5	Xi;R38-41 N;R51-53***	Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Aquatic Chronic 2 (H411) ***
bis(nonylphenyl)amine***	253-249-4	01-2119488911-28	36878-20-3	<1.5	R53	Aquatic Chronic 4 (H413)

**Additional information** Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.

**For the full text of the R-phrases mentioned in this Section, see Section 16.**

**For the full text of the H-Statements mentioned in this Section, see Section 16.**

## Section 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

**General advice** IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

**Eye contact** Rinse thoroughly with plenty of water, also under the eyelids.

**Skin contact** Remove contaminated clothing and shoes. Wash off with soap and water. Wash contaminated clothing before reuse.

**Inhalation** Move to fresh air.

**Ingestion** Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control centre immediately.



SDS # : 081072

## MAZDA ORIGINAL OIL ULTRA 5W30

Revision Date: 2015-04-14

Version 2

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Eye contact</b>	Severely irritating to eyes.***
<b>Skin contact</b>	Not classified. May produce an allergic reaction.***
<b>Inhalation</b>	Not classified. Inhalation of vapours in high concentration may cause irritation of respiratory system.
<b>Ingestion</b>	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** Treat symptomatically.

## Section 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Carbon dioxide (CO <sub>2</sub> ). ABC powder. Foam. Water spray or fog.
<b>Unsuitable Extinguishing Media</b>	Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

<b>Special hazard</b>	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.
-----------------------	--

### 5.3. Precautions for fire-fighters

<b>Special protective equipment for fire-fighters</b>	Wear self-contained breathing apparatus and protective suit.
<b>Other information</b>	Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

## Section 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

<b>General Information</b>	Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.
----------------------------	--

### 6.2. Environmental precautions



SDS # : 081072

## MAZDA ORIGINAL OIL ULTRA 5W30

Revision Date: 2015-04-14

Version 2

**General Information** Do not allow material to contaminate ground water system. Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained.

### 6.3. Methods and materials for containment and cleaning up

**Methods for cleaning up** Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

### 6.4. Reference to other sections

**Personal protective equipment** See Section 8 for more detail.

**Waste treatment** See section 13.

## Section 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

**Advice on safe handling** When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing.

**Prevention of fire and explosion** Take precautionary measures against static discharges. Ground/bond containers, tanks and transfer/receiving equipment.

**Hygiene measures** Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

### 7.2. Conditions for safe storage, including any incompatibilities

**Technical measures/Storage conditions** Keep away from food, drink and animal feedingstuffs. Keep in a bonded area. Keep container tightly closed. Preferably keep in the original container. Otherwise, reproduce all the statutory information from the labels onto the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture.

**Materials to avoid** Strong oxidising agents.

### 7.3. Specific use(s)

**Specific use(s)** No information available.\*\*\*

SDS # : 081072

## MAZDA ORIGINAL OIL ULTRA 5W30

Revision Date: 2015-04-14

Version 2

### Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

#### 8.1. Control parametres

##### Exposure limits

Mineral oil mist:

 USA: OSHA (PEL) TWA 5 mg/m<sup>3</sup>, NIOSH (REL) TWA 5 mg/m<sup>3</sup>, STEL 10 mg/m<sup>3</sup>, ACGIH (TLV) TWA 5 mg/m<sup>3</sup> (highly refined)\*\*\*

##### Legend

See section 16

#### DNEL Worker (Industrial/Professional)

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7				5.4 mg/m <sup>3</sup> /8h (aerosol - inhalation)
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)*** 93819-94-4			0.58 mg/kg Dermal 8.31 mg/m <sup>3</sup> Inhalation***	
bis(nonylphenyl)amine*** 36878-20-3			0.62 mg/kg bw/day Dermal 4.37 mg/m <sup>3</sup> Inhalation	

#### DNEL Consumer

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7				1.2 mg/m <sup>3</sup> /24h (aerosol - inhalation)
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)*** 93819-94-4			0.29 mg/kg Dermal 2.11 mg/m <sup>3</sup> Inhalation 0.24 mg/kg Oral***	
bis(nonylphenyl)amine*** 36878-20-3			0.31 mg/kg bw/day Dermal 1.09 mg/m <sup>3</sup> Inhalation 0.31 mg/kg bw/day Oral	

#### Predicted No Effect Concentration (PNEC)

Chemical Name	Water	Sediment	Soil	Air	STP	Oral



SDS # : 081072

# MAZDA ORIGINAL OIL ULTRA 5W30

Revision Date: 2015-04-14

Version 2

zinc bis[O-(6-methylhept yl)] bis[O-(sec-butyl)] bis(dithiophosphate) *** 93819-94-4	0.004 mg/l fw 0.0046 mg/l mw 0.021 mg/l or***	0.0116 mg/kg dw fw 0.00116 mg/kg dw mw***	0.00528 mg/kg soil dw***		100 mg/l***	10.67 mg/kg food***
bis(nonylphenyl)ami ne*** 36878-20-3	0.1 mg/l fw 0.01 mg/l mw 1 mg/l or	132000 mg/kg dw fw 13200 mg/kg dw mw	263000 mg/kg dw		1 mg/l	

## 8.2. Exposure controls

### Occupational Exposure Controls

#### Engineering measures

Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

#### Personal protective equipment

##### General Information

If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.

##### Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). Type A/P2. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.\*\*\*

##### Eye protection

If splashes are likely to occur, wear: Safety glasses with side-shields.

##### Skin and body protection

Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing.

##### Hand protection

Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the EC approved gloves.

### Environmental exposure controls

#### General Information

The product should not be allowed to enter drains, water courses or the soil.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Colour

amber



SDS # : 081072

# MAZDA ORIGINAL OIL ULTRA 5W30

Revision Date: 2015-04-14

Version 2

<b>Physical state @20°C</b>		Liquid	
<b>Odour</b>		No information available	
<b>Property</b>	<b>Values</b>	<b>Remarks</b>	<b>Method</b>
<b>pH</b>		Not applicable***	
<b>Boiling point/boiling range</b>		Not applicable***	
<b>Flash point ***</b>	<b>220*** °C***</b> <b>428*** °F***</b>		Cleveland Open Cup (COC) Cleveland Open Cup (COC)
<b>Evaporation rate</b>		No information available***	
<b>Flammability Limits in Air</b>		No information available	
<b>Vapour pressure</b>		No information available***	
<b>Vapour density</b>		No information available***	
<b>Density</b>	848 - *** 858 kg/m <sup>3</sup>	@ 15 °C	
<b>Water solubility</b>		Not applicable***	
<b>Solubility in other solvents</b>		No information available***	
<b>logPow</b>		No information available***	
<b>Autoignition temperature</b>		Not applicable***	
<b>Viscosity, kinematic ***</b>	<b>*** 57*** mm<sup>2</sup>/s***</b>	@ 40 °C ***	ISO 3104 ***
<b>***</b>	<b>*** 9.6 -*** 10.2 mm<sup>2</sup>/s</b>	@ 100 °C ***	ISO 3104 ***
<b>Explosive properties</b>	Not explosive		
<b>Oxidising properties</b>	Not applicable		
<b>Possibility of hazardous reactions</b>	Not applicable		

## 9.2. Other information

No information available\*\*\*

## Section 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

**General Information** No information available.\*\*\*

### 10.2. Chemical stability

**Stability** Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions** None under normal processing.

### 10.4. Conditions to Avoid

**Conditions to Avoid** Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.

### 10.5. Incompatible materials

**Materials to avoid** Strong oxidising agents.





SDS # : 081072

# MAZDA ORIGINAL OIL ULTRA 5W30

Revision Date: 2015-04-14

Version 2

## 10.6. Hazardous Decomposition Products

**Hazardous Decomposition Products** None under normal use.

## Section 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

#### Acute toxicity Local effects Product Information

<b>Skin contact</b>	. Not classified. May produce an allergic reaction.***
<b>Eye contact</b>	. Severely irritating to eyes.***
<b>Inhalation</b>	. Not classified. Inhalation of vapours in high concentration may cause irritation of respiratory system.
<b>Ingestion</b>	. Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

#### Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated heavy paraffinic***	LD50 > 5000 mg/kg bw (rat - OECD 420)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403)
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)***	LD50 2600 mg/kg (Rat)***	LD50 > 3160 mg/kg (Rabbit - OECD 402)***	
bis(nonylphenyl)amine***	LD50 > 5000 mg/kg (Rat - OECD 401)***	LD50 > 2000 mg/kg (Rat - OECD 402) ***	

#### Sensitisation

**Sensitisation** Not classified as a sensitizer.

#### Specific effects

**Carcinogenicity** This product is not classified carcinogenic. During use in engines, contamination of oil with low levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.

Chemical Name	European Union
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7	-

**Mutagenicity** This product is not classified as mutagenic.

**Reproductive toxicity** This product does not present any known or suspected reproductive hazards.

#### Repeated Dose Toxicity



SDS # : 081072

## MAZDA ORIGINAL OIL ULTRA 5W30

Revision Date: 2015-04-14

Version 2

**Subchronic Toxicity** No information available.

**Target Organ Effects (STOT)**

**Target Organ Effects (STOT)** No information available.

**Other information**

**Other adverse effects** Characteristic skin lesions (oil blisters) may develop following prolonged and repeated exposures (contact with contaminated clothing).

### Section 12: ECOLOGICAL INFORMATION

#### 12.1. Toxicity

Not classified.

#### Acute aquatic toxicity - Product Information

No information available.

#### Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7	EL50 (48h) > 100 mg/l (Pseudokirchnerella subcapitata - OECD 201)***	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)*** 93819-94-4	EbC50 (96h) 2.1 mg/l Selenastrum capricornutum (OECD 201)***	EL50 (48h) 5.4 mg/l Daphnia magna (OECD 202)***	LC50 (96h) 4.5 mg/l Oncorhynchus mykiss (OECD 203)***	
bis(nonylphenyl)amine*** 36878-20-3	EC50 (72h) > 100 mg/l (Desmodesmus subspicatus - OECD 201)***	EC50 (48h) > 100 mg/l (Daphnia magna - OECD 202)***	LC50 (96h) > 100 mg/l (Brachydanio rerio - OECD 203)***	

#### Chronic aquatic toxicity - Product Information

No information available.

#### Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7		NOEL (21d) 10 mg/l (Daphnia magna - QSAR Petrotox)***	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	

#### Effects on terrestrial organisms



SDS # : 081072

# MAZDA ORIGINAL OIL ULTRA 5W30

Revision Date: 2015-04-14

Version 2

No information available.

## 12.2. Persistence and Degradability

### General Information

No information available.

## 12.3. Bioaccumulative potential

### Product Information

No information available.

### logPow

No information available\*\*\*

### Component Information

No information available.

Chemical Name	log Pow
Distillates (petroleum), hydrotreated heavy paraffinic*** - 64742-54-7	-
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)*** - 93819-94-4	0.9***
bis(nonylphenyl)amine*** - 36878-20-3	7.7***

## 12.4. Mobility in soil

### Soil

Given its physical and chemical characteristics, the product generally shows low soil mobility.

### Air

Loss by evaporation is limited.

### Water

Insoluble. The product spreads on the surface of the water.

## 12.5. Results of PBT and vPvB assessment

### PBT and vPvB assessment

No information available.

## 12.6. Other adverse effects

### General Information

No information available.

## Section 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

#### Waste from residues / unused products

Should not be released into the environment. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations. Where possible recycling is preferred to disposal or incineration. After use, this oil must be sent to a licensed waste oil facility. Incorrect disposal of used oil poses a risk to the environment. Mixture with other waste types such as solvents, brake- and cooling liquids is forbidden.



SDS # : 081072

## MAZDA ORIGINAL OIL ULTRA 5W30

Revision Date: 2015-04-14

Version 2

<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal.
<b>EWC Waste Disposal No</b>	The following Waste Codes are only suggestions: 13 02 05. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

### Section 14: TRANSPORT INFORMATION

<u>ADR/RID</u>	not regulated
<u>IMDG/IMO</u>	not regulated
<u>ICAO/IATA</u>	not regulated
<u>ADN</u>	not regulated

### Section 15: REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

International Inventories **No information available\*\*\***

Further information

**No information available\*\*\***

#### 15.2. Chemical Safety Assessment

**Chemical Safety Assessment** No information available

#### 15.3. National regulatory information

##### **Belgium**

- Avoid exceeding occupational exposure limits (see section 8).

### Section 16: OTHER INFORMATION



SDS # : 081072

# MAZDA ORIGINAL OIL ULTRA 5W30

Revision Date: 2015-04-14

Version 2

## Full text of R-phrases referred to under sections 2 and 3

R38 - Irritating to skin

R41 - Risk of serious damage to eyes

R53 - May cause long-term adverse effects in the aquatic environment\*\*\*

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment\*\*\*

## Full text of H-Statements referred to under sections 2 and 3

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H318 - Causes serious eye damage

H411 - Toxic to aquatic life with long lasting effects

H413 - May cause long lasting harmful effects to aquatic life\*\*\*

## Abbreviations, acronyms

Legend Section 8

TWA: Time Weight Average

STEL: Short Time Exposure Limit

+ Sensitiser

\*\* Hazard Designation

M: Mutagen

\*

C:

R:

Skin designation

Carcinogen

Toxic to reproduction

Revision Date: 2015-04-14

Revision Note \*\*\* Indicates updated section.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of Safety Data Sheet