

ReinoldMax StopFire 750ml

Page 1 of 9

Last revision date: October 14, 2022

### **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

## 1.1. Product identifier

Product name: Fire Extinguishing Spray ReinoldMax StopFire 750ml

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

The product is considered for extinguishing fires of fire classes A3 (ordinary combustibles like wood, paper, textiles), B21 (flammable liquids like gasoline, alcohol), F5 (grease and fats).

Spray to extinguish small fires. Suitable to extinguish electrical appliances up to 1000V.

## 1.3. Details of the supplier of the safety data sheet

Company name:	JSC MERSETA
Street:	K. Dulksnio 9
Place:	LT-53304 Narsieciai, Kaunas, Lithuania
Telephone:	+370 37 393666
Telefax:	+370 37 393655
E-mail:	export@merseta.lt
Website:	www.reinoldmax.com

## 1.4. Emergency telephone number

Emergency institution:	In state of origin – produced in Lithuania, EU
	Toxication control and information center
	Siltnamiu 29, LT-2043 Vilnius, Lithuania
Emegency telephone:	+370 5 2362052

## **SECTION 2: Hazards identification**

#### 2.1. Classification of substance or mixture

According to Regulation (EC) No 1272/2008 of the European Parliament and of the Council and Commission Regulation (EU) 2017/776, it does not meet the criteria for classification as dangerous product.

## 2.2. Label elements

Pictogram

None



Page 2 of 9

## ReinoldMax STOP FIRE 750ml

Last revision date: October 14, 2022

## Signal word ATTENTION

## Hazard statements:

H229 The container is under pressure: may burst when heated

## **Precautionary statements:**

P102 Keep out of the reach of children P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P251 Do not pierce or burn, even after use P410 + P412 Protect from direct sunlight and do not expose to temperatures above 50 °C / 122 °F

## 2.3. Other hazards

The ingredients of this formulation do not meet the criteria for classification as PBT or vPvB substance.

## **SECTION 3: Composition/information on ingredients**

## 3.1. Substances

Not applicable

## 3.2. Mixtures

Chemical name	EC-No.	CAS-No.	Quantity %	Classification according to Regulation (EC)	REACH – Registration number
2-(2-Butoxyethoxy)- ethanol	203-961-6	112-34-5	0,4 - 0,5	Eye Irrit. 2 (H319)	No data available
Alcohols, C6-12, ethoxylated, sulfate, sodium salt	500-485-3	161025-28-1	0 - 0,1	Skin Irrit. 2, Eye Dam. 1; H315, H318	No data available
Sodium Octyl Sulfate	205-535-5	142-31-4	0 - 0,1	Skin Irrit. 2, Eye Irrit. 2; H315, H319	No data available
Water		7732-18-5	98,00	none	No data available

## MATERIAL SAFETY DATA SHEET according to Regulation (EC) No 1907/2006

Page 3 of 9

## ReinoldMax STOP FIRE 750ml

Last revision date: October 14, 2022

## **SECTION 4: First Aid Measures**

## 4.1. Description of first aid measures

General advice	Medical first aid is not necessary.
Inhalation	Inapplicable.
Skin contact	No fatal effects. Wash skin with soap and water.
Eye contact	No fatal effects. Remove contact lenses. Flush immediately eyes and under the eyelids with water.
Ingestion	No fatal effects. Do not induce vomiting without medical advice.
Additional advice	Symptomatic treatment.

## 4.2. Most important symptoms and effects, both acute and delayed

Repeated or established skin contact can cause skin irritation. Irritating to eyes.

## **<u>4.3. Identification of any immediate medical attention and special treatment needed</u> <b>Notes to physician** Treat symptomatically

## **SECTION 5: Fire Fighting Measures**

## 5.1.Extinguishing media

Suitable extinguishing media: solution is an extinguishing agent. The product is not flammable. Adjust the firefighting measures to the surroundings.

Unsuitable extinguishing media: unknown.

## 5.2. Special hazadrds arising from the substance or mixture

Special exposure hazards arising from the substance or preparation itself, its combustion products or resulting gases: unknown.

## 5.3. Advice for firefighters

Take of the cap, point and spray by using "Stop-Spray-Stop" method. This product does not require any special training before use. Usage and handling instructions are mentioned on package.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions

6.2. Environmental precautions

#### 6.3. Methods for cleaning up

Avoid contact with eyes. Inform appropriate authorities if large amounts enter drains. Wipe the foam with the cloth away with

absorbent material (such as cloth, fleece). After cleaning, rinse with water.

## MATERIAL SAFETY DATA SHEET according to Regulation (EC) No 1907/2006

Page 4 of 9

## ReinoldMax STOP FIRE 750ml

Last revision date: October 14, 2022

## 6.4. Reference to other sections

For more information, see section 8

## **SECTION 7:** Handling and Storage

7.1. Safe handling	Wash hands with soap after using fire extinguishing spray. Avoid contact with eyes. Protect pressurized container from the sunlight. Do not keep at the temperature over +50°C. Do not punch or burn the container after the use. Aluminum can is recyclable.
7.2. Safe storage 7.3. Shelf life	Storage temperature range is from 0°C to +50°C. 36 months. Expiry date is marked on the bottom of the can.

## **SECTION 8: Exposure Control and Personal Protection**

## 8.1. Parameters to be monitored None.

8.2. Additional notes on the design of technical installations

No further information, see Section 7.

**Personal protective equipment:** Avoid contact with skin, eyes and clothing. **General protective and hygienic measures:** Do not eat, drink or smoke.

## **SECTION 9: Physical and Chemical Properties**

## 9.1. Information on basic physical and chemical properties

Form Liquid Color Light straw color Odor Characteristic pH (at 20°C) 6.5-8.5 Freezing point -1°C **Boiling point** 100°C Oxidizing ability Non-corrosive Vapor tension (at 20°C) 1 Mpa Flash point Inapplicable Flammability Non-flammable Self-ignition ability Inapplicable Upper-explosion limit Inapplicable Lower-explosion limit Inapplicable Density (at 20°C) 1 g/cm3 Solubility in water 100% soluble Solubility in fats Inapplicable

## MATERIAL SAFETY DATA SHEET according to Regulation (EC) No 1907/2006

Page 5 of 9

## ReinoldMax STOP FIRE 750ml

Last revision date: October 14, 2022

Continuous working time Length of sprayed flow Temperature range Gas propellant

20-30 sec. 3-4 meters 0°C to +50°C Nitrogen (N2)

## **SECTION 10: Stability and Reactivity**

## 10.1 Reactivity

10.1. Reactivity	There are no known conditions that are likely to result in a hazardous situation.
10.2. Chemical stability	Stable under the prescribed storage conditions.
10.3. Possibility of hazardous reactions	None.
10.4. Conditions to avoid	Do not keep at the temperature over +50°C.
10.5. Incompatible materials	Oxidizing agents, acids, alkalis.
10.6. Hazardous decomposition	No data available.

## **SECTION 11: Toxicological Information**

## 11.1. Information on toxicological effects

Acute toxicity: None known.

Product Information: Product does not represent a hazard in the form of acute toxicity, according to known or provided information.

Unknown acute toxicity: Zero percent of the mixture consists of components of unknown acute toxicity.

Corrosive and irritating effects: Slightly irritating to the eyes and the skin - not subject to identification.

Sensitization: unknown.

Toxicological tests: None.

Experience from practice: No negative.

Reproductive toxicity: unknown.

Aspiration hazard: unknown.

## **SECTION 12: Ecological Information**

## 12.1. Toxicity

Zero percent of the mixture consists of components with unknown water hazard.

## 12.2. Persistence and degradability

There is no information.

## MATERIAL SAFETY DATA SHEET according to Regulation (EC) No 1907/2006

Page 6 of 9

## ReinoldMax STOP FIRE 750ml

Last revision date: October 14, 2022

## 12.3. Biokkumulationspotenzial

This solution contains a few organic fluorchemicals that have the potential to resist degradation and remain in the environment. Amount of hazardous components is too small to involve mixture to be dangerous.

## 12.4. Mobility in the ground

There is no information.

## 12.5. Other adverse effects

There is no information.

## **SECTION 13: Disposal Considerations**

#### Waste treatment methods

Disposal should be in accordance with applicable regional, national and local laws and regulations.

#### Waste code: 16 05 05

Gases in pressure vessels other than those mentioned in 16 05 04.

#### Waste key number for packaging: 15 01 04, metal packaging.

#### **SECTION 14: Transport Information**

#### Land transport (ADR/RID):

#### 14.1. UN-Number:

14.2. UN proper shipping name: 14.3. Transport hazard class(es):

Hazard label:

1950 AEROSOLS non-flammable 2.2 2.2



No

5A

190, 327 1 L P207 2.2

14.4. Packing group:	
14.5. Environmental hazards	
Danger for environment:	
14.6 Special precaution	
Classification code:	
Special Provisions:	
Limited quantity:	
Packing instructions:	
Transport category:	

## MATERIAL SAFETY DATA SHEET according to Regulation (EC) No 1907/2006

Page 7 of 9 ReinoldMax STOP FIRE 750ml Last revision date: October14, 2022 Packaging: May be packed together in an outer packaging for combination packaging: with other goods of Class 2; with goods of other classes; the mixed packing with goods which are not ADR is permitted. Other information: non-oxidizing, non-flammable, non-toxic, non-corrosive, non- asphyxiant Maritime transport IMDG: 14.1. UN-Number: 1950 14.2. UN proper shipping name: **AEROSOLS** non-flammable 2.2 14.3. Transport hazard class(es): 2.2 Hazard label: 14.4. Packing group: 14.5. Environmental hazards Danger for environment: No Marine pollutant: No **14.6 Special precaution Special Provisions:** 63,190, 327 Limited quantities: SP277 Packing instructions: P207 Stowage and handling: SW1, SW22 MS No: F-D, S-U No other applicable information (marine transport). \_\_\_\_\_ Inland waterway transport ADN: 14.1. UN-Number: 1950 14.2. UN proper shipping name: **AEROSOLS** non-flammable 2.2 14.3. Transport hazard class(es): 2.2 Hazard label:





		Page 8 of 9
ReinoldMax STOP FIRE 750ml		
Last revision date: October 14, 2022		
14.5. Environmental hazards		
Danger for environment:	No	
14.6 Special precaution		
Classification code (RID) :	5A	
Special Provisions:	19, 327	
Limited quantities (RID) :	1L	
Mixed packing provisions (RID):	MP9	
Transport category (RID) :	2	
Air transport IATA:		
14.1. UN-Number: 14.2. UN proper shipping name: 14.3. Transport hazard class(es): Hazard label:	1950 AEROSOLS non-flammable 2.2 2.2	
	Ŷ	
14.5. Environmental hazards	·	
Danger for environment:	No	
14.6 Special precaution		
PCA Limited quantities:	Y203	
PCA packing instructions:	203	
PCA max net quantity:	75kg	
CAO packing instructions:	203	
CAO max net quantity:	150kg	
Special provisions:	A1	

## **SECTION 15: Regulatory Information**

# 15.1 Safety, health and environmental regulations / legislation specific to the substance or mixture

- Section 355 (extremely hazardous substances): Substance is not listed.
- Section 313 (Specific toxic chemical listings): Substance is not listed.
- TSCA (Toxic Substances Control Act): Substance is not listed.
- · Hazardous Air Pollutants: Substance is not listed.
- · Chemicals known to cause cancer: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for females: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for males: Substance is not listed.
- · Chemicals known to cause developmental toxicity: Substance is not listed.
- · Chemicals known to cause deplete the ozone layer: Substance is not listed.
- · Chemicals known to cause persistent organic pollutants: Substance is not listed.



Page 9 of 9

## ReinoldMax STOP FIRE 750ml

Last revision date: October 14, 2022

#### Hazard pictograms: none

Signal word: Attention

#### Hazard statements:

The container is under pressure: may burst when heated

## **Precautionary statements:**

Keep out of the reach of children Do not pierce or burn, even after use Protect from direct sunlight and do not expose to temperatures above 50 °C / 122 °F

## **15.2 Chemical Safety Assessment**

The mixture was not subject to a safety assessment.

## **SEECTION16.** Other Information

#### Text of the H-phrases referred to in Section 3

H229 - The container is under pressure: may burst when heated.

Safety instructions: P102 Keep out of the reach of children P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P251 Do not pierce or burn, even after use P410 + P412 Protect from direct sunlight and do not expose to temperatures above 50 ° C / 122 ° F.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.